

(3)

924 Brake Discs

Model	Version	KW	Year	F	R	Number	HC	Ø	TH	Min TH	A	B	C
924	2.0		76-85	*		08.3963.10		257	13	11,5	84	39,8	4
924 Carrera			8.80-81	*		09.5782.10	HC	282	20,4	19,1	35,2	107	5
924 S	2.5		8.85-88	^		09.5782.10	HC	282	20,4	19,1	35,2	107	5
924 Sport			8.79-85	*		09.5782.10	HC	282	20,4	19,1	35,2	107	5
924 Turbo			11.78-85	*		09.5782.10	HC	282	20,4	19,1	35,2	107	5

F = Front Ø = Diameter Min TH = Minimum thickness B = Centering diameter
 R = Rear TH = Braking surface thickness A = Overall height C = Fixing holes number



(7)

924 Clutches and Operating Systems



924		11.75 - 07.88				
2.0	11.75-08.89	5,50	XJ, XK		3000 510 001 3082 025 531 1861 602 344 3151 193 041	215 24
2.0 Turbo, 125 kW	11.78-06.80		31.01, 02, 04		3082 087 031	225
					1861 684 132	225 23
					3151 088 201	
2.0 Turbo, 130 kW	06.80-10.86	5,50	31.03		3000 951 728 3082 087 136 1878 066 531 3151 088 201	ohne Anlasserzahnkranz / without starter gear ring 225 23
2.0 Carrera GT	06.80-10.86		31.50		3082 087 031	225
					1861 684 132	225 23
					3151 088 201	
2.5 S, 110 kW 2.5 S, 118 kW	09.85-07.87 08.87-07.88	7,50 7,50	M44.07, M44.08, M44.09, M44.10		3000 511 003 3082 087 034 1878 066 531 3151 088 201	225 23

cover assembly

release bearing



the specified work times are examples for standard vehicles

clutch disc

clutch kit



and can deviate considerably between various models.

(3)

944 Brake Discs

Model	Version	KW	Year	F	R	Number	HC	Ø	TH	Min TH	A	B	C
944	2.5		10.81-86	*		09.5782.10	HC	282	20,4	19,1	35,2	107	5
944	2.7		88-91	*		09.5783.10	HC	282	20,4	19,1	74,1	103	5
944 S	2.5 16V		86-88	*		09.5783.10	HC	282	20,4	19,1	74,1	103	5

F = Front
R = Rear

Ø = Diameter
TH = Braking surface thickness

Min TH = Minimum thickness
A = Overall height

B = Centering diameter
C = Fixing holes number



(7)

944 Clutches and Operating Systems



944		06.81 - 07.91				
2.5, 110 kW	01.85-07.87	7,90	M44.01,		3000 511 003 3082 087 034 1878 066 531 3151 088 201	225 23
2.5, 118 kW	08.87-12.90	7,90	M44.02,			
2.5, 120 kW	06.81-07.87	7,90	M44.03,			
2.7	11.88-08.89	7,50	M44.04, M44.05, M44.06, M44.07, M44.08, M44.09, M44.10, M44.11, M44.12			
2.5 S	08.86-07.88	7,50	M44.40,		3000 951 728 3082 087 136 1878 066 531 3151 088 201	ohne Anlasserzahnkranz / without starter gear ring 225 23
3.0 S2	12.88-07.91	7,80	M44.41			
2.5 Turbo, 162 kW	08.85-07.88	13,3	M44.50,		3000 513 001 3082 152 031 1862 221 032 3151 155 301	240 23
2.5 Turbo, 184 kW	09.87-07.91	13,3	M44.51, M44.52			

944 Cabriolet		12.88 - 07.91				
3.0 S2	12.88-07.91		M44.41		3000 951 728 3082 087 136 1878 066 531 3151 088 201	ohne Anlasserzahnkranz / without starter gear ring 225 23

cover assembly

release bearing



the specified work times are examples for standard vehicles

clutch disc

clutch kit



and can deviate considerably between various models.